

* SNC SERIES BANDSAWS



◀ **C-620NC**



◀ **C-7656NC**



◀ **C-520NC / C-560NC**



C-420NC ▶



C-250NC / C-300NC ▶



C-320NC ▶



C-400NC / C-460NC ▶



* Specification

Model		C-250NC	C-300NC	C-400NC	C-460NC
Capacity	Round	250 mm (10")	300 mm (12")	400 mm (16")	460 mm (18")
	Square	250 mm (10")	300 mm (12")	400 mm (16")	460 mm (18")
	Rectangular (W x H)	280 x 250 mm (11" x 10")	340 x 300 mm (13.4" x 12")	400 x 400 mm (16" x 16")	460 x 460 mm (18" x 18")
Bundle Capacity	Width	155 ~ 200 mm	190 ~ 300 mm	215 ~ 295 mm	220 ~ 360 mm
	Height	50 ~ 120 mm	70 ~ 140 mm	100 ~ 190 mm	95 ~ 230 mm
Saw Blade	Speed	20 ~ 100 m/min (66 ~ 328 fpm)			
	Size (L x W x T)	3505 x 27 x 0.9 mm (138" x 1.06" x 0.035")	3820 x 34 x 1.1 mm (150.4" x 1.3" x 0.042")	4570 x 41 x 1.3 mm (180" x 1.6" x 0.05")	4670 x 41 x 1.3 mm (184" x 1.6" x 0.05")
	Tension	Hydraulic (Automatic blade breaking detection)			
Motor Output	Saw Blade	3 HP (2.5 kw)	5 HP (3.75 kw)	7.5 HP (5.5 kw)	7.5 HP (5.5 kw)
	Hydraulic	1 HP (0.75 kw)	1 HP (0.75 kw)	2 HP (1.5 kw)	2 HP (1.5 kw)
	Coolant	1/6 HP (0.1 kw)	1/8 HP (0.1 kw)	1/4 HP (0.19 kw)	1/4 HP (0.19 kw)
Hydraulic Tank		20 l (5.3 gal.)	25 l (6.6 gal.)	40 l (10.6 gal.)	40 l (10.6 gal.)
Coolant Tank		45 l (11.9 gal.)	45 l (11.9 gal.)	80 l (21 gal.)	80 l (21 gal.)
Vise Control		Hydraulic		Hydraulic Full Stroke Cylinder	
Automatic Indexing Length	Single	403 mm (15.9")	403 mm (15.9")	593 mm (23.3")	593 mm (23.3")
	Multiple	MAX. 6500 MM (MAX. 650")			
	Rest Piece	50 mm (2")	50 mm (2")	90 mm (3.5")	90 mm (3.5")
Height of Work Bed		660 mm (26")	660 mm (26")	750 mm (29.5")	750 mm (29.5")
Net Weight		1450 kgs	1600 kgs	2550 kgs	2700 kgs
Gross Weight		1650 kgs	1800 kgs	2750 kgs	2900 kgs
Floor Space		1890 x 1850 mm (74.5" x 72.5")	1890 x 1905 mm (74.5" x 75")	2450 x 2310 mm (96" x 91")	2450 x 2310 mm (96" x 91")

* Specification

Model		C-320NC	C-420NC	C-520NC	C-560NC	C-620NC	C-7656NC
Capacity	Round	320 mm (12.6")	420 mm (16.5")	520 mm (20.5")	560 mm (22")	620 mm (24.4")	560 mm (22")
	Square	320 mm (12.6")	420 mm (16.5")	520 mm (20.5")	560 mm (22")	620 mm (24.4")	560 mm (22")
	Rectangular (W x H)	380 x 320 mm (15" x 12.6")	420 x 420 mm (16.5" x 16.5")	560 x 520 mm (22" x 20.5")	600 x 560 mm (23.6" x 22")	760 x 620 mm (30" x 24.4")	760 x 560 mm (30" x 22")
Bundle Capacity	Width	190 ~ 300 mm	190 ~ 360 mm	250 ~ 470 mm	250 ~ 470 mm	600 ~ 700 mm	250 ~ 500 mm
	Height	70 ~ 140 mm	100 ~ 190 mm	150 ~ 315 mm	150 ~ 315 mm	180 ~ 390 mm	265 ~ 400 mm
Saw Blade	Speed	20 ~ 100 m/min (66 ~ 328)					
	Size (L x W x T)	4240 x 34 x 1.1 mm (167" x 1.33" x 0.04")	4770 x 41 x 1.3 mm (187.8" x 1.6" x 0.05")	6040 x 54 x 1.6 mm (238" x 2.1" x 0.06")	6040 x 54 x 1.6 mm (238" x 2.1" x 0.06")	7200 x 54 x 1.6 mm (283" x 2.1" x 0.06")	6664 x 54 x 1.6 mm (262" x 2.1" x 0.06")
	Tension	Hydraulic (Automatic blade breakage detection)					
Motor Output	Saw Blade	5 HP (3.7 kw)	7.5 HP (5.6 kw)	7.5 HP (5.6 kw)	10 HP (7.5 kw)		10HP (7.5 kw)
	Hydraulic	1 HP (0.75 kw)	2 HP (1.5 kw)	2 HP (1.5 kw)		2 HP (1.5 kw)	
	Coolant	1/8 HP (0.1 kw)	1/8 HP (0.1 kw)	1/4 HP (0.19 kw)		1/4 HP (0.19 kw)	
Hydraulic Tank		25 l (6.6 gal.)	40 L (10.6 gal.)	40 l (10.6 gal.)		50 l (13 gal.)	
Coolant Tank		45 l (11.9 gal.)	85 l (22.5 gal.)	85 l (22.5 gal.)		85 l (21.25 gal.)	
Vise Control		Hydraulic	Hydraulic full stroke cylinder				
Automatic Indexing Length	Single	403 mm (15.9")	503 mm (19.8")	600 mm (23.6")	600 mm (23.6")	600 mm (23.6")	503 mm (19.8")
	Multiple	Max. 6500 mm (max. 650")					
	Rest Piece	50 mm (2")	60 mm (2.4")	90 mm (3.5")	90 mm (3.5")	160 mm (6.3")	200 mm (7.9")
Height of Work Bed		790 mm (31")	700 mm (27.5")	690 mm (27.2")	690 mm (27.2")	600 mm (23.6")	280 mm (26.8")
Net Weight		2000 kgs	3000 kgs	3700 kgs	3700 kgs	4800 kgs	6000 kgs
Gross Weight		2200 kgs	3300 kgs	4300 kgs	4300 kgs	5400 kgs	6600 kgs
Floor Space		2010 x 2000 mm (79" x 79")	2490 x 2360 mm (98" x 93")	2400 x 2766 mm (94.5" x 105")	2400 x 2677 mm (94.5" x 105")	2200 x 3700 mm (8606" x 145.6")	2330 x 3890 mm (92" x 153")